



Street / Sanitation / Recycling  
705 South River Road  
West Lafayette, IN 47906  
Phone: (765) 775-5242  
Fax: (765) 746-1302

August 28, 2012

The West Lafayette Street Department is requesting sealed bids for one street sweeper meeting the enclosed specifications.

SEALED BIDS will be received until 8:30 a.m. (local time) on September 18, 2012 at the Office of the Clerk-Treasurer, City Hall, 609 West Navajo St., West Lafayette, IN 47906. Each bidder will submit his bid upon forms provided in the bid packet and enclosed in a sealed envelope marked, "Street Sweeper". At 8:30 a.m., all bids will be taken to the Board of Works meeting to be opened and read aloud in the City Hall Council Chambers, 609 W. Navajo St., West Lafayette, IN 47906.

For a bid to be considered complete, the following items must be submitted:

1. Bid Price Sheet.
2. Specifications Check Sheet, Items #1 through #28 completed.
3. State Form 95 (Revised 1987) with properly executed non-collusion affidavit.
4. Bid bond or cashier's check made out to the City of West Lafayette, Indiana in the amount of 5% of bid price.

Bidder will attach any explanations and/or detail of specifications provided on a separate page(s).

**City of West Lafayette  
Street Sweeper Bid**

**BID FORM 1 OF 3  
BID PRICE SHEET**

ITEM	UNIT PRICE	QUANTITY	TOTAL AMOUNT
Base Price			
Option (if applicable) Costs			
Discounts or Other Price Adjustments			
Destination Charges			
Dealer Preparation Charges			
Any Additional-Allowance			
Trade-In Allowance			
<b>TOTAL BID</b>			

Bidder: \_\_\_\_\_  
                    Company

Signature: \_\_\_\_\_ Title: \_\_\_\_\_  
                    Name

Date: \_\_\_\_\_

# City of West Lafayette

## BID FORM 2 of 3 BID SPECIFICATONS CHECK SHEET Street Sweeper

**INSTRUCTIONS:** The specifications herein describe the **minimum acceptable features and performance requirements** for a street sweeper to be purchased by the West Lafayette Street Department. Bidders are to have thoroughly read and understood these specifications prior to bid submission. If any part of an item is not in compliance, an explanation can be provided on a separate sheet with the benefits of that item to the City. It will be up to the purchasers' discretion what items will be termed equal. Bids shall be good for a minimum of 90 days.

Bidders shall place a check mark in the specification column to indicate if the item being bid is exactly as specified. If an item is left blank, the City will assume the bidder cannot meet the specifications and may cause rejection of the bid.

By checking any of the "NO" spaces the bidder states that the product being bid does not conform to that specification. All variations and/or exceptions must be documented, referencing applicable paragraph(s), and explained in detail on a separate page titled "Exceptions". If the City of West Lafayette determines by any means that exceptions exist which were not identified on such list, then that bid will be disqualified as being non-responsive. If no exceptions are taken, it will be assumed that the bid meets all specifications as stated.

Complete the following check sheet items #1 through #28.

Sign and Date on page 10.

### **SPECIFICATIONS: Three Wheel Mechanical Street Sweeper.**

The sweeper to be furnished under this proposal shall be a three wheel mechanical type, front wheel steer, single engine, high dump hopper, full hydrostatic drive, 5.6 cubic yard hopper capacity with dual gutter broom system. It shall be the manufacturer's latest model and design. These specifications shall be regarded as MINIMUM. Bidders must furnish all descriptive literature, manufacturer's compliance certificates and all other necessary data on the equipment proposed as required in the specification. Bidder must also include an Indiana User's List consisting of a minimum of ten municipalities that are using the current model being bid.

1. HOPPER		YES	NO
1.1	Hopper capacity shall be 5.6 cubic yards		
1.2	Hopper shall have a lifting capacity of 12,000 lbs.		
1.3	Hopper shall be constructed of grade 304 <b>stainless steel</b> to permit longer life and lower the cost of operation, the debris hopper excluding the dump chute, shall carry a <b>lifetime warranty</b> for as long as the customer owns the sweeper. The		

	warranty shall include but not be limited to, the floor, sides, roof and discharge door. The warranty shall cover rust, corrosion and abrasion perforation, including normal wear and tear. Manufacturer will be financially responsible for all repairs, parts and labor, including protective coatings for the life of the sweeper. 100% parts and labor. No pro-rating or hour limitations acceptable. Vendors shall supply with their bid, a warranty statement from the manufacturer.		
1.4	Hopper dump system shall have a safety lockout system to prevent any forward or reverse movement of the sweeper with hopper in the raised position.		
1.5	Hopper shall be raised and lowered by means of two 4" diameter hydraulic cylinders.		
1.6	Hopper shall have a load discharge door which will open automatically when hopper is being raised and close automatically when hopper is being lowered.		
1.7	Hopper dump control shall be by means of a single cab dash mounted rocker switch.		
1.8	A seal shall be provided between the hopper and the elevator to prevent dirt and dust emission.		
1.9	Hopper shall be a high dumping type, 114" minimum.		

**2. CAB**

**YES**

**NO**

		YES	NO
2.1	Cab shall be fully enclosed and of all steel construction.		
2.2	Cab shall be mounted front and center of sweeper for safety and unobstructed, panoramic, operator vision.		
2.3	Cab shall be attached to chassis frame by means of rubber mounts.		
2.4	Cab shall be dust and weather sealed and be equipped with factory installed air conditioning, heater and defroster.		
2.5	Grab handles shall be supplied on the front of the cab.		
2.6	Cab interior shall be sound suppressed and insulated with an in-cab noise level not exceeding 83 dBA.		
2.7	Cab shall be furnished with two seats, one being the primary operator's station and the other for the purpose of operator training.		
2.8	Operator's seat shall be single bucket air suspension type with cloth upholstery, dual arm rests, and shock absorbers.		
2.9	Both operator's seat and "buddy" seat shall have three point safety seat belts with shoulder and lap harnesses.		
2.10	For operator safety and comfort, the front of seat to the front wall of cab shall be a minimum of 23", maximum 31".		
2.11	For operator safety and comfort, the cab rear wall to cab front wall shall be a minimum of 56 1/2".		
2.12	For operator safety and comfort, the back seat to center line of steering column shall be a minimum of 17", maximum 31".		
2.13	Cab shall have a single lever operated tilt and telescoping steering wheel.		
2.14	For operator's safety, cab shall have sliding windows on both right and left sides.		
2.15	Cab shall have adequate storage space for driver's tool kit and hard hat.		
2.16	Cab shall have dual west coast mirrors with extended frames and 12" convex sweeping mirrors on both sides. Sweepers that require a seat change during operation must have remote power adjustable		

	mirrors.		
2.17	Cab shall have tinted safety glass throughout and a single full width tinted sun visor.		
2.18	Cab shall be furnished with a full width interior ceiling shelf to accommodate a radio, documents and other equipment.		

**3. ENGINE**

**YES**

**NO**

3.1	Sweeper shall be powered by a single Tier 3, 4-cylinder, turbo charged four cycle diesel engine with a minimum horsepower rating of 115 HP @ 2500 engine RPM. Cubic inch displacement shall be 276 CID and net torque rating of 274 ft. lbs. at 1400 RPM. All sweeper functions and drive systems shall be powered by this engine.		
3.2	Engine shall have a two stage dry type air cleaner with safety element and restriction indicator. Plus TURBO II pre-cleaner or equal.		
3.3	Engine shall be water cooled by aid of a radiator of swing-away design.		
3.4	Antifreeze protection for engine shall be not less than minus 34 degrees Fahrenheit.		
3.5	Engine shall automatically shut down and dispose itself from re-starting if any attempt is made to unlatch radiator away from its locked position.		
3.6	Engine shall be protected against damage by means of an anti-crank device which will prevent re-engagement of starter while the engine is running.		
3.7	Engine shall be fitted with a pusher fan with special "ejector" blades for centrifugal ejection of ambient dust particles from the engine compartment.		

**4. TRACTION SYSTEM**

**YES**

**NO**

4.1	Traction system shall be fully hydrostatic and capable of variable speeds up to 25 MPH.		
4.2	Direction and speed selection shall be controlled by means of a dash mounted four position quadrant shifter which is electronically controlled.		
4.3	Engine mounted traction pump shall be variable displacement axial piston type.		
4.4	Broom and elevator speed shall be independent of vehicle speed.		
4.5	The traction drive system shall be capable of being shifted from "LOW" to "HIGH" while the sweeper is in motion.		
4.6	The traction pump and motors shall be relief valve protected.		
4.7	Operational road speed control shall be by means of a single automotive type foot pedal.		
4.8	The traction system shall provide braking assistance when control pedal is released.		
4.9	The rear wheel motor and torque hub drive system shall be a carrier beam type <b>with rubber spring and torque rod suspension.</b>		

**5. ELEVATOR**

**YES**

**NO**

5.1	The elevator shall be 7 flight configuration with continuously molded rubber belts and replaceable corded rubber squeegee tips. Belt type conveyors systems will not be deemed as equal.		
5.2	Elevator sprockets shall be of split flange type to enable replacement without having to remove belts and shafts.		
5.3	Elevator sprockets shall have hardened teeth for longevity.		
5.4	Elevator flight bars shall be constructed of 2" x ½" aluminum angle.		
5.5	Elevator speed shall be variable and reversible.		
5.6	Elevator belt shafts shall be of split design to facilitate easy belt replacement.		
5.7	Elevator motor drive shall be direct hydraulic (no chain or sprockets) with relief cartridge protection.		
5.8	Elevator shall have an adjustable floor and deflector system to ensure even hopper loading and prevent back spilling.		
5.9	Elevator floor shall incorporate an 'open/close' bulk material entry gate system, operator controlled from inside the cab.		
5.10	Elevator drive shall be from its own dedicated, directly driven hydraulic pump.		
5.11	Elevator shall have a hydrant flush system.		
5.12	Elevator drive system shall incorporate a positive drive using Sprockets or cogs. Friction drive systems are not acceptable.		

**6. HYDRAULIC SYSTEM**

**YES**

**NO**

		YES	NO
6.1	Hydraulic oil reservoir system shall consist of two frame mounted tower tanks, each with an oil capacity of 18 gallons. The residual oil capacity shall be an additional 5 gallons for a total system capacity of 41 gallons.		
6.2	To provide dependable performance and reduce maintenance costs, the hydraulic system MUST include the following filtration elements:	--	
6.2.(1)	A 40 micron tank fill neck strainer in each tank		
6.2.(2)	Each tank MUST have its own suction strainer rated at a minimum 100 mesh.		
6.2.(3)	A suction filter with restriction gauge MUST be supplied with a minimum rating of 10 microns		
6.2.(4)	A high pressure filter complete with restriction status indicator shall be supplied.		
6.2.(5)	A water / hydraulic oil separator / filter shall be installed in the return circuit.		
6.3	Each hydraulic tank shall be provided with a 5 psi. pressurized fill cap.		
6.4	Each hydraulic tank shall have rear mounted, accessible drain plugs.		
6.5	Hydraulic manifolds, valves and solenoids shall be mounted in a separate dedicated, enclosed compartment, away from dirt and debris, for protection and ease of access.		
6.6	Triple Pump Hydraulic System-includes one pump dedicated to the pickup broom, one pump dedicated to the elevator system, and one pump dedicated to the lift functions and gutter broom rotation.		

<b>7. PICKUP BROOM</b>		<b>YES</b>	<b>NO</b>
7.1	Pickup broom shall be 32" diameter and 58" long minimum.		
7.2	Pickup broom drive shall be direct hydraulic, variable speed with relief valve protection.		
7.3	Pickup broom shall be hydraulically raised and lowered by a single, in cab dash mounted rocker switch.		
7.4	Pickup broom shall be self-adjusting for pressure and wear.		
7.5	Pickup broom motor shall have a shaft and seal protection device which will prevent the ingress of damaging wire, cassette tape, fishing line, etc.		
7.6	Pickup broom width shall match elevator width. Sweepers that attempt to funnel debris onto a narrow belt will not be accepted.		

<b>8. GUTTER BROOMS</b>		<b>YES</b>	<b>NO</b>
8.1	Gutter brooms (right & left sides) shall be a minimum of 47" in diameter and each shall contain twelve snap-in. "Tuff Grip" disposable steel tine segments.		
8.2	Gutter broom drive shall be completely hydraulic and relief valve protected.		
8.3	Gutter brooms shall be hydraulically lowered and raised by means of an in-cab, dash mounted rocker switch.		
8.4	Provisions shall be made for gutter broom pressure adjustment by means of independent dash mounted electrical switch gauges.		
8.5	Gutter brooms shall be free floating both horizontally and vertically and shall be impact protected.		
8.6	Gutter broom curb angle adjustment shall be by simple multi hole and anchor pin arrangement. Adjustment shall be "wrench free".		
8.7	Gutter broom support towers shall have adjustable travel "stop" mechanisms to limit inward travel of gutter brooms.		
8.8	Gutter broom motors shall have a shaft and seal protection device which will prevent the ingress of damaging wire, cassette tape, fishing line, etc.		

<b>9. WATER SYSTEM</b>		<b>YES</b>	<b>NO</b>
9.1	Water tank capacity shall be 230 gallons minimum.		
9.2	Water tank shall be constructed of cross-linked corrosion proof material.		
9.3	A low water indicator shall be dash mounted in cab.		
9.4	Individual, adjustable, variable flow, water delivery valves shall be installed in the sweeper cab to allow operator to control water sprays over main broom and both gutter brooms.		
9.5	Twin electric diaphragm pumps with total output rating of 4 gallons per minute @ 35 PSI shall be supplied.		
9.6	An in line 20 mesh screen type filter shall be installed in an accessible area and shall be capable of being checked, cleaned or changed without the use of tools.		
9.7	A 15' hydrant hose, coupler and wrench shall be supplied.		
9.8	A high/low water flow switch shall be installed in the cab for additional water flow control.		

<b>10. FUEL SYSTEM</b>		<b>YES</b>	<b>NO</b>
10.1	Vehicle fuel system must include a 35 gallon diesel fuel tank. (minimum)		
10.2	Fuel system must incorporate a fuel and water separator with built in primary fuel filter.		

<b>11. DIRT SHOES</b>		<b>YES</b>	<b>NO</b>
11.1	Dirt shoes shall be of parallel arm design, polyethylene construction and be capable of floating over uneven surfaces, railroad tracks, raised manhole covers, etc.		

<b>12. BRAKES</b>		<b>YES</b>	<b>NO</b>
12.1	Service brakes shall be internal expanding shoe and drum type on rear wheels.		
12.2	Parking brake shall be mechanically applied and hydraulically released internal expanding type.		
12.3	Parking brake shall be automatically applied when sweeper is placed in "PARK" position.		
12.4	Brake master cylinder shall have an auxiliary boost feature.		
12.5	Standard braking system shall be assisted by vehicle's inherent dynamic braking when control pedal ("GO" Pedal) is released.		

<b>13. STEERING</b>		<b>YES</b>	<b>NO</b>
13.1	Steering shall be hydrostatic type, by means of an engine driven gear pump through a hydraulic cylinder and shall be capable of operation in the event of engine shutdown.		

<b>14. FRONT (STEERING) AXLE / SPINDLE</b>		<b>YES</b>	<b>NO</b>
14.1	Front axle assembly shall be spindle type, with dual wheels and tires.		
14.2	Front axle configuration shall be such that the standard front steering road wheels shall be not be closer than 40 inches to the curb line when sweeping, to avoid tire damage from broken bottles and other sharp debris.		
14.3	Front axle assembly shall incorporate a weight and load matched 'Rubber Spring' and torque rod suspension system.		
14.4	Rear wheel motor and torque hub carrier beam axle, shall be furnished with full 'Rubber Spring' and torque rod suspension.		

<b>15. FRAME</b>		<b>YES</b>	<b>NO</b>
15.1	Frame shall be constructed of 4 gauge, high strength low alloy steel (ASTM 607 or equivalent) with an RBM rating of 863,700 inch pounds and a minimum yield strength of not less than 50,000 psi.		
15.2	Frame shall be 13" x 3" 'C' section channel.		

15.3	Frame shall incorporate front tow points.		
15.4	A tool/storage compartment shall be built into right rear fender.		
15.5	Frame attached gutter broom towers shall have reinforced cut outs to enable access to lower elevator bearings for ease of maintenance.		

**16. ELECTRICAL SYSTEM 12 VOLT**

**YES**

**NO**

16.1	Battery shall be maintenance free and rated at 900 CCA.		
16.2	A heavy duty 120 amp dust shielded alternator shall be supplied.		
16.3	All electrical connections shall be sealed and heat shrunk with epoxy resin connectors. <b>No-splice</b> wiring between connectors.		
16.4	A sealed electrical systems locker shall be provided to house all controlling electrical components and protect them from exposure to dirt, moisture, and inclement weather.		
16.5	The system locker shall comprise of a sealed compartment to house both high amperage and low amperage components.		
16.6	All components within the locker shall be easily replaceable with minimum effort.		
16.7	All rocker switches in cab shall be sealed, back lit, and function identified.		
16.8	All electrical system diodes shall be located within the systems locker.		
16.9	A laminated electrical control unit diagram shall be attached to systems locker door for instant easy reference during troubleshooting or repair procedures.		
16.10	Two sealed beam headlights with in-dash high beam indicator shall be standard.		
16.11	Two speed windshield wipers shall be provided.		
16.12	Sweeper shall be supplied with dual stop and tail light combinations, dual gutter broom lights, rear license plate light and bracket, back up lights and reflectors, self-canceling turn signals with hazard flashers, electrical back up alarm (107 dBA minimum) and hopper dump alarm (107 dBA minimum), cab strobe with limb guard and halogen arrowstik.		
16.13	Solenoids for hydraulic manifolds shall be enclosed in rear fender compartment for protection and easy access.		
16.14	All electrical wiring shall be solid colored, numbered and function coded every 12" for quick, easy identification purposes.		

**16 SWEEPER BODY**

**YES**

**NO**

17.1	Sweeper body shall have hinged, swing out single latched side panels for simple, easy access to elevator, fuel tank fill and water manifold components		
17.2	Rear radiator grille and engine cover shall have stainless steel hinges to enhance longevity and eliminate rust.		
17.3	A heavy duty front bumper shall be supplied.		
17.4	A rust and corrosion proof front grille shall be supplied.		
17.5	A two-step cab entry ladder with anti-slip, positive grip feature shall be supplied.		

**18. WHEELS AND TIRES**

**YES**

**NO**

18.1	Front rims shall be 6.75 HC, 10 hole heavy duty steel disc type with 10R 17.5 G load range radial tires		
18.2	Rear rims shall be disc type 8.25 X 22.5 with 11R 22.5 G load range radial tires.		

**19. SUSPENSION**

**YES**

**NO**

19.1	A rear drive motor carrier with <b>full rubber spring and torque rod suspension</b> shall be supplied.		
19.2	Front (steering) axle assembly shall incorporate a weight and load matched ' <b>Rubber Spring</b> ' and <b>torque rod suspension system</b> .		

**Suspension must be a full suspension, incorporating the entire sweeper.**

**20. CAB DASH & INSTRUMENTS**

**YES**

**NO**

20.1	An automotive style, anti-glare, wrap-around dash with easily removable fascia and instrument panel shall be supplied.		
20.2	All dash mounted equipment including instruments, gauges, switches and display panels shall have extra length wires to permit lifting of dash for internal component access.		
20.3	Dash panel shall have a light emitting diode panel system which will monitor and provide an alert to the following systems: OIL PRESSURE, SWEEPER in PARK, RIGHT HYDRAULIC TANK LEVEL, LEFT HYDRAULIC TANK LEVEL, RIGHT AND LEFT TURN SIGNALS and HIGH BEAM INDICATOR. The panel shall also be capable of accommodating additional monitoring systems if required.		
20.4	The dash board shall be of low cut design for completely unobstructed vision.		
20.5	The dash panel shall incorporate high flow adjustable side and windshield defrost vents.		
20.6	The side instrument panel shall accommodate all sweeping functions, heating and air conditioning controls.		
20.7	An automatic rear view camera with full color LCD monitor shall be supplied. The camera shall be equipped infra-red lamps to allow for night vision.		
20.8	The sweeper shall incorporate an ERGO switch function. This function will allow the operator to activate all sweeping components using one switch. The ERGO switch will be capable of shutting down all sweeping components, as well as water, using the same ERGO switch. Must be one switch design.		

**21. SWEEPER DIMENSIONS**

**YES**

**NO**

21.1	Sweeper shall meet the following minimum requirements:	--	--
21.2	Wheel Base..... 116 in.		
21.3	Turning Radius (Not to exceed).....12.5 ft.		
21.4	Overall Length (Not to exceed).....214 in.		

21.5	Maximum Height (Not to exceed).....118 in.		
21.6	Maximum Width (Not to exceed)..... 98 in.		
21.7	Sweeping Swath.....125 in.		
21.8	Maximum Weight/Empty.....14,440 lbs		

**22. PAINT**

**YES NO**

22.1	All sweeper components, including but not limited to, CAB, HOPPER, FRAME, ELEVATOR, BODY PANELS, ENGINE COVER PANELS, BODY FLOOR PANELS, GENERAL BRACKETRY, shall be individually 100% powder coated BEFORE VEHICLE ASSEMBLY to protect the machine from the adversities of weather and the ravages of sweeping environments.		
22.2	Sweeper standard color shall be White.		

**23. QUALITY**

**YES NO**

23.1	ALL fasteners above 1/4" in thread size shall be grade #8 or better.		
23.2	ALL critical fasteners shall be torqued to manufacturer's quality requirements and a special torque striping paste shall be applied as witness to this procedure.		
23.3	ALL hydraulic hose pressure fittings shall be torqued to manufacturer's requirements.		
23.4	The sweeper shall be manufactured by a company with an internationally recognized and registered quality system which shall meet or exceed I.S.O. 9001 standards		

**24. WARRANTY**

**YES NO**

24.1	Sweeper shall carry a one year warranty covering 100% parts and labor with all repairs to be carried out at customer's location.		
------	----------------------------------------------------------------------------------------------------------------------------------	--	--

**25. MANUALS**

**YES NO**

25.1	The following documentation shall be supplied upon delivery of unit:	--	--
a)	<b>Sweeper:</b> 1-Parts Manuals, 1-Service/Operation Manuals, 1-Operator's Guide		
b)	<b>Engine:</b> 1-Engine Users Guide.		

**26. TRAINING**

**YES NO**

26.1	Operator/mechanic training shall be provided at no charge by dealer at customer's location.		
------	---------------------------------------------------------------------------------------------	--	--

**27. ADDITIONAL EQUIPMENT TO BE SUPPLIED**

**YES NO**

26.1	Cab Strobe with Limb Guard		
26.2	Rear Halogen Arrow-stik with Limb Guard		
26.3	AM/FM/CD Stereo		
26.4	Elevator Flush		

26.5	Hopper Flush		
------	--------------	--	--

**28. TRADE-IN OPTION**

**YES**

**NO**

28.1	Trade-In: 1999 dual steer Sterling cab with Swartze A7000 street sweeper body with 51,463 miles.		
------	--------------------------------------------------------------------------------------------------	--	--

Bidder: \_\_\_\_\_  
Company

Signature: \_\_\_\_\_ Title: \_\_\_\_\_  
Name

Date: \_\_\_\_\_

# BID, OFFER OR PROPOSAL FOR SALE OR LEASE OF MATERIALS

Bid Form 3 of 3

(Defined at I.C. 36-1-2-9.5)  
(Please type or print)

- Date: \_\_\_\_\_
1. Governmental Unit: CITY OF WEST LAFAYETTE
  2. County: TIPPECANOE
  3. Bidder (Firm): \_\_\_\_\_  
     Address: \_\_\_\_\_  
     City/State: \_\_\_\_\_
  4. Telephone Number: \_\_\_\_\_
  5. Agent of Bidder (if applicable): \_\_\_\_\_

Pursuant to notices given, the undersigned offers bid(s) to City of West Lafayette (Governmental Unit) in accordance with the following attachment(s) which specify the class or item number or description, quantity, unit, unit price and total amount.

The contract will be awarded by classes or items, in accordance with specifications. Any changes or alterations in the items specified will render such bid void as to that class or item. Bidder promises that he has not offered nor received a less price than the price stated in his bid for the materials included in said bid. Bidder further agrees that he will not withdraw his bid from the office in which it is filed. A certified check or bond shall be filed with each bid if required, and liability for breach shall be enforceable upon the contract, the bond or certified check or both as the case may be.

\_\_\_\_\_  
Signature of Bidder or Agent

## BID OFFER OR PROPOSAL

Attach separate sheet listing each item bid based on specifications published by governing body. Following is an example of the bid format: REFER TO BID PRICE SHEET

Class or Item	Quantity	Unit	Description	Unit Price	Amount

## NON-COLLUSION AFFIDAVIT

STATE OF INDIANA )  
                          ) ss:  
\_\_\_\_\_ COUNTY )

The undersigned bidder or agent, being duly sworn on oath, says that he has not, nor has any other member, representative, or agent of the firm, company, corporation or partnership represented by him, entered into any combination, collusion or agreement with any person relative to the price to be bid by anyone at such letting nor to prevent any person from bidding nor to induce anyone to refrain from bidding, and that this bid is made without reference to any other bid and without any agreement, understanding or combination with any other person in reference to such bidding.

He further says that no person or persons, firms, or corporation has, have or will receive directly or indirectly, any rebate, fee, gift, commission or thing of value on account of such sale.

\_\_\_\_\_  
Bidder (Firm)

\_\_\_\_\_  
Signature of Bidder or Agent

Subscribed and sworn to before me this \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_.

My commission Expires: \_\_\_\_\_

County of Residence: \_\_\_\_\_

\_\_\_\_\_  
Notary Public

## ACCEPTANCE

There now being sufficient unobligated appropriated funds available, the contracting authority of \_\_\_\_\_ (Governmental Unit) hereby accepts the terms of the attached bid for classes or items numbered \_\_\_\_\_ and promises to pay the undersigned bidder upon delivery the price quoted for the materials stipulated in said bid.

Contracting Authority Members: \_\_\_\_\_

Date: \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



## **NOTICE TO BIDDERS**

### **Street Sweeper**

Notice is hereby given that the Board of Public Works and Safety of the City of West Lafayette, Indiana will receive sealed bids until the hour of 8:30 a.m. (local time) on September 18, 2012, at the Office of the Clerk-Treasurer, City Hall, 609 W. Navajo St., West Lafayette, IN 47906 for one 2013 street sweeper, as per specifications. After said time, all bids will be taken to the City Hall Council Chambers and there will be publicly opened and read aloud. Bids received after said time will be returned unopened. No oral, telegraph, facsimile, or telephone bids or changes to bids will be considered.

Specifications and bid forms are available on the City website at [www.westlafayette.in.gov](http://www.westlafayette.in.gov), at the Street Dept., 705 S. River Rd., West Lafayette, phone 775-5242, or at the Office of the Clerk-Treasurer.

Each bidder will submit his bid upon forms provided in the bid packet and enclosed in a sealed envelope marked, "Street Sweeper."

The bid must be accompanied by a bidders bond or certified check of not less than 5% of the total bid made in favor of the City of West Lafayette, Indiana

The Board of Public Works and Safety expressly reserves the right to reject any or all bids and waive irregularities of bidding.

BOARD OF PUBLIC WORKS AND SAFETY  
JUDITH C. RHODES  
CLERK-TREASURER

PUBLISH: August 31, 2012, and September 7, 2012